ENGINEERING DEPARTMENT UNIVERSITY OF DELHI DELHI-110007

Ref. No. UE/ 85

4

/DU/M- 54 (2018-2019)
NOTICE INVITING QUOTATION

dated

9/12/12

Sealed percentage rate quotation are hereby invited from the contractor enlisted with CPWD, MES, Railways and working contractor of Delhi University for the work "Urgent repair work of ceiling in kitchen and toilet in D-19 and repair of gate at C-31 (29-31) Probyn Road, University of Delhi. So as to reach the office of the undersigned upto 3.00 P.M. on.....

5 mm cement plaster on the rough side of single or half brick wall of mix: 1:4 (1 cement: 4				Amount
ine sand)	12	sqm	189,40	2272.80
8 mm cement plaster in two coats under layer 12 mm thick cement plaster 1:5 (1 cement : 5 oarse sand) finished with a top layer 6 mm thick cement plaster 1:6 (1 cement : 6 fine sand).	8	sqm	240.55	1924.40
distempering with 1st quality acrylic distemper (ready mixed) of approved manufacturer, of equired shade and colour complete, as per manufacturer's specification. Two or more coats in new work	58	sqm	50.65	2937.70
temoving dry or oil bound distemper, water proofing cement paint and the like by scrapping, and papering and preparing the surface smooth including necessary repairs to scratches etc. omplete.	38	sqm	9.90	376.00
ainting with synthetic enamel paint of approved brand and manufacture of required colour to ive an even shade: One or more coats on old work	18	sqm	48.50	873.00
oisposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by nechanical means, including loading, transporting, unloading to approved municipal dumping round or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including Il lifts involved.	5	cum	123.70	619.00
roviding and applying birla / JK wall putty on wall surface (one or more coats) as required in hickness 1 mm i/c sand papering etc to prepare smooth as per direction of Engineer-inharge.	30	sqm	65.00	1950.00
epair steel gate i/c welding , M.S. flats etc complete.	2	each	1547.00	3094.00
			Total	14046.90
			Sav	14047.00
The state of the s	8 mm cement plaster in two coats under layer 12 mm thick cement plaster 1:5 (1 cement: 5 carse sand) finished with a top layer 6 mm thick cement plaster 1:6 (1 cement: 6 fine sand). Sistempering with 1st quality acrylic distemper (ready mixed) of approved manufacturer, of equired shade and colour complete, as per manufacturer's specification. Two or more coats in new work Semoving dry or oil bound distemper, water proofing cement paint and the like by scrapping, and papering and preparing the surface smooth including necessary repairs to scratches etc. complete. Sainting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: One or more coats on old work Sisposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by nechanical means, including loading, transporting, unloading to approved municipal dumping round or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including Il lifts involved. Toviding and applying birla / JK wall putty on wall surface (one or more coats) as required in nickness 1 mm i/c sand papering etc to prepare smooth as per direction of Engineer-in-harge. Sepair steel gate i/c welding, M.S. flats etc complete.	8 mm cement plaster in two coats under layer 12 mm thick cement plaster 1:5 (1 cement : 5 to coarse sand) finished with a top layer 6 mm thick cement plaster 1:6 (1 cement : 6 fine sand). 158 parse sand) finished with a top layer 6 mm thick cement plaster 1:6 (1 cement : 6 fine sand). 158 parse sand) finished with a top layer 6 mm thick cement plaster 1:6 (1 cement : 6 fine sand). 158 parse sand papering with 1st quality acrylic distemper (ready mixed) of approved manufacturer, of sequired shade and colour complete, as per manufacturer's specification. Two or more coats in new work 159 parse sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete. 160 papering and preparing the surface smooth including necessary repairs to scratches etc. complete. 170 papering with synthetic enamel paint of approved brand and manufacture of required colour to sive an even shade: One or more coats on old work. 170 parse sand) finished with a top layer 6 mm thick cement plaster 1:6 (1 cement: 5 in example 1) approved manufacturer, of sequired coats in new work. 180 parse sand) finished with a top layer 6 mm thick cement plaster 1:6 (1 cement: 5 in example 2) approved manufacturer, of sequired in sequired in plaster 1:6 (1 cement: 5 in example 2) approved manufacturer, of sequired in sequired in plaster 1:6 (1 cement: 6 fine sand). 181 parse sand plaster 1:6 (1 cement: 6 fine sand). 182 parse sand plaster 1:6 (1 cement: 6 fine sand). 183 parse sand plaster 1:6 (1 cement: 6 fine sand). 184 parse sand plaster 1:6 (1 cement: 6 fine sand). 185 parse sand plaster 1:6 (1 cement: 6 fine sand). 185 parse sand plaster 1:6 (1 cement: 6 fine sand). 186 parse sand plaster 1:6 (1 cement: 6 fine sand). 187 parse sand plaster 1:6 (1 cement: 6 fine sand). 188 parse sand papering and papering approved by scrapping approved by scrappin	8 mm cement plaster in two coats under layer 12 mm thick cement plaster 1:5 (1 cement : 5 to arse sand) finished with a top layer 6 mm thick cement plaster 1:6 (1 cement : 6 fine sand). 8 sqm bistempering with 1st quality acrylic distemper (ready mixed) of approved manufacturer, of squired shade and colour complete, as per manufacturer's specification. Two or more coats in new work squired shade and colour complete, as per manufacturer's specification. Two or more coats in new work squired preparing the surface smooth including necessary repairs to scratches etc. somplete. 8 and papering and preparing the surface smooth including necessary repairs to scratches etc. somplete. 8 and papering and preparing the surface smooth including necessary repairs to scratches etc. somplete. 8 and papering and preparing the surface smooth including necessary repairs to scratches etc. somplete. 9 also proved by a sqm squired colour to squired and manufacture of required colour to squired in size and even shade: One or more coats on old work. 9 also proved by Engineer-in-charge, beyond 50 m initial lead, for all leads including lifts involved. 18 and papering etc to prepare smooth as per direction of Engineer-in-charge. 19 and papering etc to prepare smooth as per direction of Engineer-in-charge. 10 and papering etc to prepare smooth as per direction of Engineer-in-charge. 10 and papering etc to prepare smooth as per direction of Engineer-in-charge. 10 and papering etc to prepare smooth as per direction of Engineer-in-charge. 10 and papering etc to prepare smooth as per direction of Engineer-in-charge. 11 and papering etc to prepare smooth as per direction of Engineer-in-charge.	8 mm cement plaster in two coats under layer 12 mm thick cement plaster 1:5 (1 cement : 5 to arse sand) finished with a top layer 6 mm thick cement plaster 1:6 (1 cement : 6 fine sand). 10 sistempering with 1st quality acrylic distemper (ready mixed) of approved manufacturer, of equired shade and colour complete, as per manufacturer's specification. Two or more coats in new work emoving dry or oil bound distemper, water proofing cement paint and the like by scrapping, and papering and preparing the surface smooth including necessary repairs to scratches etc. complete. ainting with synthetic enamel paint of approved brand and manufacture of required colour to like sqm with synthetic enamel paint of approved brand and manufacture of required colour to like sqm with synthetic enamel paint of approved brand and manufacture of required colour to like sqm with synthetic enamel paint of approved brand and manufacture of required colour to like sqm with synthetic enamel paint of approved brand and manufacture of required colour to like sqm with synthetic enamel paint of approved brand and manufacture of required colour to like sqm with synthetic enamel paint of approved brand and manufacture of required colour to like sqm with synthetic enamel paint of approved brand and manufacture of required colour to like sqm with synthetic enamel paint of approved brand and manufacture of required colour to like sqm with synthetic enamel paint of approved brand and manufacture of required colour to like sqm with synthetic enamel paint of approved brand and manufacture of required colour to like sqm with synthetic enamel paint of approved brand and manufacture of required colour to like sqm with synthetic enamel paint of approved brand and manufacture of required colour to like sqm with synthetic enamel paint of approved by approved by Engline of ap

`Condition:

- 1 The work should be completed in 10 days.
- 2 1.5% water charges will be deducted.
- 3 Rates should be quoted both in words & figures.
- 4 The contractor must visit the site before quoting his rates.
- 5 CPWD specification in force will be followed.
- 6 Undersigned reserves the authority to reject any or all the quotation without assigning any reason therefore.

Executive Engineer

I/we hereby quote...... % above/below/at par on the estimated cost of Rs.14047/-

Undertaking:

I/we hereby undertake that my/our agency have not been black listed/debarred in any Govt. organization since last 3 years.

(Contractor)

Copy to:-

- 1 The Director, Computer Center with a request to display the Notice Inviting quotation on the Delhi University Website.
- 2 Sh. Jacob John, J.E. (C)
- Mrs. Kavita, JACT to ensure the display of the quotation notice on University website.
- 4 Notice Board

Executive Engineer