

ENGINEERING DEPARTMENT
UNIVERSITY OF DELHI
DELHI-110007
NOTICE Re-INVITING QUOTATIONS

Ref. No. UE/ 392

/DU/M- 88

(2015-2016)

dated 31-12-15

Sealed item rate quotations are hereby Re-invited from the contractors enlisted with CPWD, MES, Railways and any Govt./ public sector undertaking and working contractor of Delhi University for the work " Misc. repair work in sports room store, room no. 108 and Science Lab of School etc in CIE Building and repairing damaged boundary wall at back side of ARC Building, Dismantling steel near Warden House of Mansarowar Hostel, University of Delhi. " So as to reach the office of the undersigned upto 3.00 P.M. on 5-1-16

S. No	Description of Items	Unit	Qty	Rate	Amount
1	Steel work welded in built up sections/ framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer using structural steel etc. as required. In gratings, frames, guard bar, ladder, railings, brackets, gates and similar works	kg	40		
2	Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq. meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground within 50 metres lead : With cement mortar 1:4 (1 cement : 4 fine sand)	sqm	24		
3	Renewing glass panes, with putty and nails wherever necessary including racking out the old putty: Float glass panes of thickness 4 mm	sqm	2		
4	Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.	sqm	460		
5	Distemping with 1st quality acrylic washable distemper (ready made) of approved manufacturer and of required shade and colour complete. As per manufacturer's specification. One or more coats on old work	sqm	220		
6	Finishing walls with Acrylic Smooth exterior paint of required shade Old work (Two or more coat applied @ 1.67 ltr/ 10 sqm) on existing cement paint surface	sqm	240		
7	15 mm cement plaster on the rough side of single or half brick wall of mix 1:4 (1 cement: 4 fine sand)	sqm	45		
8	Distemping with 1st quality acrylic distemper (ready mixed) of approved manufacturer, of required shade and colour complete, as per manufacturer's specification. Two or more coats on new work	sqm	80		
9	Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved.	cum	8		
10	Earth work in excavation by mechanical means (Hydraulic excavator) / manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m. All kinds of soil.	cum	22		
11	Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 m and lift upto 1.5 m.	cum	10		
12	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level 1:5:10 (1 cement : 5 coarse sand : 10 graded stone aggregate 40 mm nominal size)	cum	3		
13	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in foundation and plinth in: Cement mortar 1:6 (1 cement : 6 coarse sand)	cum	20		
14	Dismantling steel work in built up sections in angles, tees, flats and channels including all gusset plates, bolts, nuts, cutting rivets, welding etc. including dismembering and stacking within 50metres lead.				

15	Repair ceiling plaster RCC surface i/c removing the loose concrete and applying water proofing treatment with Dr. Fixit compound on the rough surface with ceiling plaster bottom layer 1:3 (1cement: 3 C. sand) and top layer 1:3 (1cement: 3 fine sand) total thickness at the plaster 15 to 25 mm etc complete as per direction of Engineer-in-charge.	sqm	15
16	Taking out/ refixing welding hinges grill taking at site etc complete	Job	2
17	P/F fibre sheet (4 mm thick) roofing wall putty coated J or L hooks nuts and bolts etc complete.	sqm	3
18	Uprooting stay unwanted vegetation/ peepal tree etc from CC pavement and building sides and making good the same as per existing finishing as directed by Engineer-in-charge.	each	6

Total Rs.

Condition:

- 1 The work should be completed in 25 days.
- 2 1.50 % water/ electric charges will be deducted.
- 3 Rates should be quoted both in words & figures.
- 4 Undersigned reserves the authority to reject any or all the quotation without assigning any reason therefore
- 5 SC/ ST contractors should enclose copies of attested caste certificate otherwise their quotation will not be accepted.
- 6 Contractor should enclose the copy of Labour Licence, Registration with EPFO, ESIC & BOCW Welfare Board otherwise their quotation will not be accepted



Executive Engineer

I/we hereby undertake that my/our agency have not been black listed/debarred in any Govt. organization since last 3 years.

Contractor

- 1 The Director, Computer Center with a request to display the Notice Inviting Quotation on the Delhi University Website.
- 2 Sh. Jacob John J.E. (C)
- ✓ 3 Ms. Kavita, J.A.C.T. to ensure the display of the tender notice on University website
- 4 Notice Board.



Executive Engineer